

## TANDEM KIPER

MODEL		TA 8040	TA 10041	TA 8045 XXL	TA 11045 XXL	TA 14045 XXL SPECIAL	TA 14045/2 XXL	TA 16045 XXL SPECIAL	TA 16045/2 XXL	TA 18045/2 XXL	TA 20051 SPECIAL	TA 20051/2 XXL	TA 23061/2 XXL
Bruto masa	kg	8.000	10.190	8.000	11.000	13.900	13.900	16.000	16.000	18.000	20.000	20.000	20.500
Neto masa	kg	2.050	2.190	2.580	2.750	3.100	3.300	3.400	3.600	3.800	4.500	4.640	6.000
Opterećenje ruda	kg	1.000	1.450	1.000	1.450	1.700	1.700	2.000	2.000	2.000	2.000	2.000	2.500
Visina platforme sa std kotačima, bez tereta	mm	1.080	1.060	1.080	1.080	1.100	1.100	1.100	1.100	1.110	1.360	1.360	1.450
Unutarnje dimenzije platforme	mm	4.070 x 2.080	4.070 x 2.080	4.480 x 2.150/2.250	4.480 x 2.150/2.250	4.480 x 2.150/2.250	4.480 x 2.150/2.250	4.480 x 2.150/2.250	4.480 x 2.150/2.250	4.480 x 2.150/2.250	5.080 x 2.340/2.410	5.080 x 2.340/2.410	6.0500 x 2.340/2.410
Visina stranice	mm	500	500	500	500	600	600	600	600	600	800	800	800
Visina dodatnih stranica	mm	500	500	500	500	600	600	600	600	600	800	800	800
Utovarni kapacitet	m3	8,5	8,5	9,9	9,9	11,8	11,8	11,8	11,8	11,8	19,3	19,3	23
Kvadratna osovina	mm	70	70	70	70	90	90	90	90	90	100	120	150
Gaz kotača	mm	1.550	1.550	1.800	1.800	1.800	1.800	1.800	1.800	1.800	2.000	2.000	2.000
Broj podiznih cilindara	kom	1	1	1	1	1	2	1	2	2	1	2	2
Promjer	mm	75/90/105	75/90/105	60/75/90/105	75/90/105/120	75/90/105/120	60/75/90/105	75/90/105/120	60/75/90/105	60/75/90/105	90/105/120/140	75/90/105/120	75/90/105/120
Visina podizanja cilindra	mm	1.400	1.400	1.800	1.800	1.800	1.600	1.800	1.600	1.800	1.800	1.800	2.000
Bočni kut kipanja	°	45	45	45	45	45	45	45	45	45	45	45	45
Stražnji kut kipanja	°	45	45	49	49	49	45	49	45	49	49	49	>50
Potrebna količina ulja	L	10	10	11	15	15	20	15	20	22	23	28	37
Standardni kotači		11.5/80 - 15.3 (10)	15.0/55 - 17 (10)	15.0/55 - 17 (10)	15.0/55 - 17 (10)	500/50 - 17 (14)	500/50 - 17 (14)	500/50 - 17 (18)	500/50 - 17 (18)	445/45 R19.5	385/65 R22.5	385/65 R22.5	385/65 R22.5